


Differences between V4 and V5 GPM products and possible bias correction of GMI precipitation retrievals based on precipitation system size and intensity

Abishek Adhikari and Chuntao Liu

Texas A&M University – Corpus Christi (PMM 2017)



Objectives:

- Compare the precipitation retrieval differences between Version5 (V5) and Version4 (V4) products by using Precipitation Features (PF) date sets.
- To investigate the possibility of using size and minimum 89 GHz PCT to improve GMI precipitation retrieval.

Data and Methods:

- The V4 and V5 data (January 2015 to December 2016) from GPM Combine and GMI has been used for the study
- The algorithm used to define the Precipitation Feature (PFs) is similar to that described in Liu et al. 2008. The DPR precipitation radar and GMI precipitation features (DPR-RGPFs) are defined by grouping the contiguous collocated pixels with precipitation detected by either combine algorithm or GMI surface precipitation rate greater than 0.1 mm hr⁻¹.
- Volumetric precipitation from GMI and Combine are inter-compared in DPR-RGPFs of different sizes, and depths.




Fig 1: Zonal distribution of total volumetric precipitation from Combine and GMI over (a) ocean, (b) land. The solid and dashed lines are V5 and V4 products respectively.




Fig 2: Distribution of total volumetric precipitation with sizes from Combine and GMI over (a) ocean, (b) land. The solid and dashed lines are V5 and V4 products respectively.




Fig 3: Two-dimensional histogram of area and ratio of Combine and GMI volumetric Precipitation of DPR-RGPFs over Ocean (left) and over Land (right) using V5 (a & b), V4 (c & d), and difference between V5 & V4 (e & f) products.




Fig 5: Difference between accumulated Combine and GMI volumetric precipitation using V5 (upper) and V4 (lower) products.




Fig 6: Geographical distribution of population of small (top), large (middle) and shallow (bottom) DPR-RGPFs with factor of two difference between volumetric precipitation of Combine and GMI. Left panels are V4 and Right panels are V5 products.

Bias calculation and correction:

- Bias factor is calculated by finding ratios of Combine and GMI volumetric precipitation with consideration of size and Minimum 89 GHz PCT of DPR-RGPFs

$$\text{Bias Factor} = \frac{\sum \text{Volprecip}_{\text{Combine}}}{\sum \text{Volprecip}_{\text{GMI}}}$$

- created with DPR-RGPFs in 40°S-40°N separately over ocean and land. The samples with elevations above 2 km are removed.

- These bias factors are used to correct the GMI volumetric precipitation.
- Biases corrected GMI = Volprecip_{GMI} * bias factor




Fig 7: Histogram of ratios between accumulated precipitation of Combine and GMI in compared to min 85 GHz PCT and PFs size over ocean (left) and over land(right).




Fig 8: Zonal distribution of total volumetric precipitation from Combine, GMI, and Corrected GMI over (a) ocean, (b) land.




Fig 9: Two-dimensional histogram of area and ratio of Combine and GMI volumetric Precipitation of DPR-RGPFs over land (left) and over ocean (right) after the bias correction.




Figure 10: Difference between accumulated Combine and Corrected GMI volumetric precipitation

Figure 11: Seasonal variation of Percentage differences of Combine and GMI volumetric precipitation before(left) and after(right) the bias correction.

Summary:

- V5 GMI has significant improvement and more consistent with combined product over both land and ocean.
- V5 GMI is still higher than Combined in large DPR-RGPFs over land. Probably related to strong ice scattering.
- The increase of precipitation in small systems is one improvement in V5.
- GMI precipitation retrieval estimates could be improved and make it more consistent with Combine by using a simple bias correction based upon the area and minimum 89 GHz PCT. This simple bias correction is more promising over tropics.

Acknowledgements:

This research was supported by NASA Precipitation Measurement Mission grants NNX16AD76G under the direction of Dr. Ramesh Kakar and NNX16AH74G under the direction of Dr. Erich Stocker. Thanks to the Precipitation Processing System (PPS) team at NASA Goddard Space Flight Center, Greenbelt, MD, for data processing assistance.